



Product facts


- Shoreditch aluminium glazing bars can be applied to single or double glazed Shoreditch Edition screens
- Single glazed version Optima 117 plus Shoreditch Edition
- Double glazed version Revolution 54
 Shoreditch Edition
- Dry jointed and fully demountable
- Door options Single glazed or double glazed Edge pivoting glass door, or Kinetic Align sliding glass door with Kinetic Shoreditch Edition only
- Manufactured at Optima's UK factory in Bath

Acoustics


- Rw38dB for Optima 117 plus –
 Shoreditch Edition, using 12.8mm acoustic laminated glass
- Rw45dB for Revolution 54 –
 Shoreditch Edition, using 2 x
 12.8mm acoustic laminated glass

Deflection


 Can accommodate up to ±40mm deflection (±25mm for Kinetic Align)




Vertical section through Optima 117 plus single glazed Shoreditch screen




Vertical section through Revolution 54 double glazed Shoreditch screen




Vertical section showing double glazed Edge Symmetry door



Vertical section showing single glazed Kinetic Shoreditch glazing and Kinetic Align door



Vertical section through single glazed butt jointed glass



Vertical section through double glazed butt jointed glass

Product overview

| System type | Single glazed: Optima 117 plus Shoreditch Edition and Kinetic Shoreditch Edition Double glazed: Revolution 54 Shoreditch Edition | |
|--------------------------|---|--|
| Head detail | Single glazed: Standard aluminium head channels available 25mm or 50mm deep (50mm only for Kinetic Shoreditch Edition) Double glazed: 25mm x 54mm or 50mm x 54mm standard aluminium head channel | |
| Base detail | Single glazed: Standard aluminium base channels available 25mm or 50mm deep Double glazed: 25mm x 54mm or 50mm x 54mm standard aluminium base channel | |
| Deflection head options | Single glazed and double glazed 2-part internal deflection heads: ±25mm – 90mm deep aluminium channel ±40mm – 135mm deep aluminium channel | Single glazed and double glazed 2-part external deflection heads: ±25mm – 94mm deep aluminium channel ±40mm – 140mm deep aluminium channel Note: ±25mm only for Kinetic Shoreditch Edition |
| Door options | Edge Symmetry or Affinity single or double glazed framed door Kinetic Align sliding glass door (Kinetic Shoreditch Edition only) | |
| Glass thickness | Single glazed: 10mm, 10.8mm, 12mm, 12.8mm and 16.8mm thick glass available as standard, subject to panel width, height and acoustic rating Double glazed: Minimum thickness 10mm toughened glass, maximum thickness 12.8mm acoustic laminated glass. Thickness subject to panel width, height and acoustic rating | |
| Maximum screen height | Single glazed: Maximum ceiling height 3000mm subject to build configuration and access into building using 12.8mm acoustic laminated glass. Greater heights up to 4m can be achieved with 16.8mm laminated glass. Please speak to our Technical Team Double glazed: Maximum ceiling height 3000mm subject to build configuration and access into building | |
| Acoustic rating | Single glazed: Rw33dB – 12mm toughened glass Rw38dB – 12.8mm acoustic laminated glass Rw40dB – 16.8mm acoustic laminated glass Double glazed: Rw41dB – 12mm toughened glass + 12.8mm acoustic laminated glass Rw45dB – Two layers of 12.8mm acoustic laminated glass Doors: Rw35dB – single glazed Edge Symmetry Rw41dB – double glazed Edge Symmetry Rw39dB – single glazed Edge Affinity Rw42dB – double glazed Edge Affinity | |
| | Rw36dB – Kinetic Align | |





Optima

Optima Partitions LLC
Unit 1106
Level 11
Marina Plaza
Dubai Marina
United Arab Emirates

- T. Sales & Technical: 00971 45631300
- E. Action.GCC@OptimaSystems.com
- W. OptimaSystems.ae